






NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

THE HAND'O'LOCK QUICK COUPLER ALLOWS THE FAST REPLACEMENT OF THE ATTACHMENT TOOLS. THANKS TO ITS SIMPLE AND STRONG FRAME IT CAN RELY ON AN EXCELLENT QUALITY-PRICE RATIO. IN ITS HYDRAULIC VERSION WITH ITS **DOUBLE ACTION** SYSTEM, IT ENABLES THE FULLY AUTOMATIC LOCKING AND UNLOCKING OPERATIONS.

| MECHANIC | | | TONS (LB) | 0,6 - 1,2 (1323 - 2646) | | 0,6 - 4,0 (1323 - 8818) | | 4,0 - 10,0 (8818 - 22046) | |
|---------------|---|------|--------------|----------------------------|-------|----------------------------|-------|------------------------------|--------|
| A. A. | | MOD. | | CW 00 | | CW 05 | | CW 10 | |
| | 0 | Α | MM (IN) | 144 | (5,7) | 175 | (6,9) | 305 | (12) |
| - FO - | C | В | MM (IN) | 150 | (5,9) | 200 | (7,9) | 300 | (11,9) |
| A | В | С | MM (IN) | 30 | (1,2) | 40 | (1,6) | 50 | (2) |
| W//O COURT ED | | | KG (LB) | 10 | (22) | 14 | (31) | 42 | (93) |

| HYDRAULIC DOUBLE | | E ACTION | TONS (LB) | 0,6 - 4,0 (1323 - 8818) | | 4,0 - 10,0 (8818 - 22046) | | 7,5 - 15,0) (16535 - 33069) | | 15,0 - 25,0) (33069 - 55116) | |
|------------------|-------------|----------|--------------|----------------------------|--------|------------------------------|--------|---------------------------------|---------|----------------------------------|---------|
| Ŀ | T T | | MOD. | CW 0 | 5 D.E. | CW 1 | 0 D.E. | CW 2 | 0S D.E. | CW 2 | 0 D.E. |
| | | 0 | A MM (IN) | 175 | (6,9) | 305 | (12) | 420 | (16,5) | 550 | (21,6) |
| | | | B MM (IN) | 200 | (7,9) | 300 | (11,9) | 475 | (18,7) | 475 | (18,7) |
| - | A | В | C MM (/N) | 40 | (1,6) | 50 | (2) | 60 | (2,3) | 60 | (2,3) |
| | | | KG (LB) | 15 | (33) | 43 | (95) | 110 | (242,5) | 180 | (396,8) |
| Q | W/O COUPLER | | bar (psi) | 250 | (3626) | 250 | (3626) | 250 | (3626) | 250 | (3626) |
| | MAX | | | | | | | ON RI | EQUEST | ON RE | EQUEST |





OPTIONAL

1 HYDRAULIC INSTALLATION KIT

WITH THE HYDRAULIC QUICK COUPLER THE INSTALLATION KIT CAN BE PROVIDED, INCLUDING SOLENOID VALVE AND ELECTRIC SWITCH WITH MAGNETS TO EASILY PUT IT INSIDE THE CAB

2 LIFTING HOOK

A HOOK APPROVED FOR LIFTING OPERATIONS CAN BE WELDED DIRECTLY ON THE QUICK COUPLER. THE HOOK VERSION 2A CAN ONLY BE INSTALLED IF THE EXCAVATOR IS NOT ALREADY EQUIPPED WITH LIFTING PROVISIONS ON THE CONNECTING ROD

NB* THE LIFTING CAPACITY OF THE HOOK IS ADJUSTED ACCORDING TO THE SUPPORT TO WHICH THE HOOK IS APPLIED

3 CW ON HINGE

RECOMMENDED APPLICATION ON BUCKETS.

CW FOR TILTING BUCKETS

RECOMMENDED APPLICATIONS ON TILTING BUCKETS.

5 REVERSE CW

RECOMMENDED APPLICATION ON FLAT PLATES, SUCH AS ADAPTER PLATES, MULCHERS, SHEARS, ETC.

6 REVERSIBLE CW

RECOMMENDED APPLICATIONS ON BUCKETS USED IN BACK OR FRONT DIGGING WORKS.



W/O COUPLER

