



**NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)**

THE AR FAST LOCK PATENTED QUICK COUPLER ENABLES THE FAST LOCKING AND UNLOCKING OF THE ATTACHMENT TOOLS, CONSIDERABLY REDUCING THE TIME FOR THEIR REPLACEMENT. THE MECHANICAL VERSION IS PROVIDED WITH A SEMI-AUTOMATIC SYSTEM THAT REQUIRES THE MANUAL INTERVENTION WHEN THE TOOL HAS TO BE RELEASED. BOTH THE LOCKING AND THE SAFE BLOCKING OF THE NEW TOOL ARE AUTOMATIC OPERATIONS. IN THE HYDRAULIC VERSION THESE FUNCTIONS ARE MANAGED DIRECTLY FROM THE CAB.

	TONS (LB)	0,6 - 1,8 (1323 - 3968)	1,8 - 2,5 (3968 - 5512)	2,5 - 4,0 (5512 - 8819)	4,0 - 6,0 (8819 - 13228)	6,0 - 7,5 (13228 - 16535)
MOD.		AR15	AR30	AR40	AR50	AR70
<b>A</b> MM (IN)		206 (8,1)	226 (8,9)	238 (9,4)	271 (10,7)	317 (12,5)
<b>B</b> MM (IN)		156 (6,1)	181 (7,1)	196 (7,7)	218 (8,6)	258 (10,2)
<b>C</b> MM (IN)		92 (3,6)	92 (3,6)	97 (3,8)	120 (4,7)	124 (4,9)
<b>Ø</b> MM (IN)		30 (1,2)	35 (1,4)	35 (1,4)	40 (1,6)	45 (1,8)

MECHANIC SEMI-AUTOMATIC			AR15 S.A.	AR30 S.A.	AR40 S.A.	AR50 S.A.	AR70 S.A.
	W/O COUPLER	KG (LB)	16 (35)	20 (44)	25 (55)	30 (66)	61 (135)

HYDRAULIC SINGLE ACTION			AR15 S.E.	AR30 S.E.	AR40 S.E.	AR50 S.E.	AR70 S.E.
	W/O COUPLER	KG (LB)	18 (40)	22 (49)	27 (60)	32 (71)	63 (139)
	MAX	BAR (PSI)	250 (3626)	250 (3626)	250 (3626)	250 (3626)	250 (3626)



**OPTIONAL**

- 1 HYDRAULIC INSTALLATION KIT**  
WITH THE HYDRAULIC QUICK COUPLER THE INSTALLATION KIT CAN BE PROVIDED, INCLUDING SOLENOID VALVE AND ELECTRIC SWITCH WITH MAGNETS TO EASILY PUT IT INSIDE THE CAB
- 2 LIFTING HOOK**  
UPON REQUEST, A LOADING HOOK WILL BE FITTED, COVERED WITH AN APPROVAL ON THE CONFORMITY DECLARATION OF OUR PRODUCT.  
**NB\* THE LIFTING CAPACITY OF THE HOOK IS ADJUSTED ACCORDING TO THE SUPPORT TO WHICH THE HOOK IS APPLIED. THIS CAPACITY IS INDICATED IN THE PRODUCT'S OWNER'S MANUAL.**
- 3 AR ADAPTER**  
THE ADAPTER APPLIED TO ANY TOOL ENABLES THE COUPLING WITH THE AR FAST LOCK QUICK COUPLER.